



AECHELON TECHNOLOGY

**611 Gateway Blvd, Suite 300
South San Francisco, CA 94080**

Nucleus 10.0 G Datasheet

LIMITED RIGHTS AND DISTRIBUTION STATEMENT

The Government's rights to use, modify, reproduce, release, perform, display, or disclose these technical data are restricted by paragraph (b) of DFAR clause 252.227-7015, Technical Data--Commercial Items. Any reproduction of this technical data or portions thereof marked with this legend must also include this statement.

Overview



Nucleus 10.0 Chassis

System Detail

The following table highlights the details of the Nucleus system hardware.

Component	Description
Dimensions	7" x 17.2" x 29" (H x W x D) *Rail Kit between 26.5" and 36.4" deep (square and round hole support)
Weight	88 lbs.
CPU	Xeon® Scalable Processor
System Memory	320 GB
Video Output	NVIDIA RTX Ampere®; primary system: 2 – 7 channels + 1 Front End; 8 channels for secondary systems DisplayPort (1.4) typical formats: 2560x1600@120Hz and 4K e-Shift 120Hz
Storage	87 TB (RAID 5 protected) + Hot Spare

Ports	2 x RJ45 1GBase-T 2 x RJ45 10GBase-T 2 x SFP 6 x USB 3.0 1 x RS-232
Max Power Consumption	3,494 Watts / 11,914 BTU/h (Config: 8 GPU @ 4k120, Fan 100%, 200V)
Operating System	SHB Windows 11 IoT Enterprise
Operating Environment	Operating Relative Humidity: 8% to 90% (non-condensing) Operating Temperature: 10°C to 35°C (50°F to 95°F)
Non-operating Environment	Non-operating Relative Humidity: 5% to 95% (non-condensing) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)
MTBF	

Power

Nucleus optimal voltage is 208/230V 50/60Hz (2+2) redundant power with IEC C14 receptacles. The Nucleus can be run at 120V 50/60Hz on each if the four Titanium rated power supplies, but redundancy will be lost in this configuration. Up to 2 of the power supplies can be powered from a 20 AMP circuit.

Volatility Statement

Nucleus Nodes include non-volatile cache storage for the RAID controllers. Before returning any IG for repair from a classified environment, it is best practice to remove the cache vault first.

Storage Type	Volatility	Usage
Motherboard - DRAM ²	Volatile	System Memory
Motherboard - Flash ROM ¹	Non-Volatile	BIOS/Firmware
Raid Controller - Flash ROM ¹	Non-Volatile	BIOS/Firmware
Raid Controller - Cache	Non-Volatile	Temporary Data Cache
SSD	Non-Volatile	User Data

Encryption

Nucleus is able to provide encryption of data at rest with self-encrypting drives (SEDs). The SEDs adhere to the TCG Enterprise and OPAL 2.0 Security Subsystem Class specification.

Accessories Included

- Four NEMA 5-15P to IEC C13 power cords per each IG
- Rail Kit
- External USB-DVD
- OS System Recovery Drive

Options

Aechelon Part No.	Description
004-0007-001	Rack, 24U, 600mm x 1070mm (APC AR3104)
002-0114-001	PDU, 2U 208V 3ph, NEMA L21-30, Metered (Server Technology, Inc. C2WG24SN-YCLN5D6) - Requires a rack.
006-0072-002	Cable, 16/3, IEC C13 to IEC C14, 6 ft (Stay Online 9768)

Rack Considerations

The NFPA (National Fire Protection Association) sets the rack clearance in front and behind to be a minimum of 36".

¹ Flash ROM is used for the Firmware and BIOS and contains no user data.

² DRAM volatility only occurs when power is completely removed from an IG for more than 60 seconds.